

3500-4000V DC Square Body

Size 600

gRB - gRD from 6 to 125 A

Catalog Numbers, Ratings

Size	Current Rating I_N (A)	Interrupting I_N (A)	Watts Loss		Catalog Number	Ref. No.	
			$0.8 I_N$	I_N			
600	6	@ 3500 V DC 30kA L/R = 30 ms	5.3	9.5	CC 35 gRB 600 QF 0006	S083736	
	8		7	12.7	CC 35 gRB 600 QF 0008	R083735	
	10		10.2	18.5	CC 35 gRB 600 QF 0010	N089390	
	12		11	20	CC 35 gRB 600 QF 0012	V082220	
	16		13.1	24	CC 35 gRB 600 QF 0016	P089391	
	20		14	25.4	CC 35 gRB 600 QF 0020	Q089392	
	25		18	32.5	CC 35 gRB 600 QF 0025	R089393	
	32		@ 4000 V DC 30kA L/R = 30 ms	25.5	46	CC 40 gRB 600 QF 0032	A086963
	40			35	63	CC 40 gRB 600 QF 0040	B086964
	50			29	52	CC 40 gRB 600 QF 0050	C086965
	63			42	76.5	CC 40 gRB 600 QF 0063	D086966
	80			51	92	CC 40 gRB 600 QF 0080	E086967
	80		@ 4000 V DC 30kA L/R = 30 ms	3.9	67	CC 40 gRD 600 QF 0080	B075763
	100			50.5	88	CC 40 gRD 600 QF 0100	C075764
	125			63	110	CC 40 gRD 600 QF 0125	D075765

Microswitch: 2R 3E 1-5N BS Ref. Number: J310025



Ratings:

Volts : 3500VDC
 : 4000VDC
 Amps : 6 to 125A
 IR : 30kA I.R.
 L/R : 30mSec

Dimensions

